

IDENTIFICATION GUIDE FOR DRIVE SHAFTS



Size	Cross and bearing kit	Inboard yoke	Profile pairing	Guard tubes	Guard cones
LINE W / LINE W...E					
W 2100 W 100 E			 00a* 00c 0a 0v 1	 SD05 SD15	 SD05 SD15
W 2200 W 200 E			 00a* 00cH 0a 0v 1	 SD05 SD15	 SD05 SD15
W 2300 W 300 E			 0v 1 1b 2a	 SD15 SD25 SD25/1	 SD15 SD25
W 2400 W 400 E			 1b 2a S4LH S5	 SD25 SD25/1	 SD25
W 2500			 S4 S5	 SD25 SD25/1	 SD25
W 2600			 S4V S5 S5H S6	 SD25 SD35	 SD25 SD35
W 2700			 S2 x 47(25)H	 SD35	 SD35
LINE W WITH WIDE ANGLE JOINT ON ONE SIDE WWE / ON TWO SIDES WWZ					
WW 2280			 00aGA** 00cGA 0aG 0vGA 1G	 SD05 SD15	 SD05/SD15 SDF15 SDF15
WW 2380			 0vGA 1G 1bGA 2aG	 SD15 SD25 SD25/1	 SD15/SD25 SDF15 SDF15 SDF25 SDF25/20
WW 2480			 1bGA 2aG S4LGA S5	 SD25 SD25/1	 SD25 SDF25/20 SDF25/20
WW 2580			 S4GA S5	 SD25 SD25/1	 SD25 SDF25/20 SDF25/20
LINE P POWERDRIVE					
P 400			 1bH 2a S4LH S5	 PG20	 PG20
P 500			 S4LH S5 S4V S5	 PG20	 PG20
P 600			 S5H S6	 PG30	 PG30
P 700			 S5H S6	 PG30	 PG30
P 800			 60 x 55 (28) H	 PG30V	 PG30V
LINE P WITH WIDE ANGLE JOINT ON ONE SIDE PME / ON TWO SIDES PWZ					
PW 480			 1bGA 2aG S4LGA S5	 PG20	 SDF25/20 SDF25/20
PW 580			 S4GA S5	 PG20	 SDF25/20 SDF25/20
PW 675			 S4GA S5 S5H S6H	 PG20 PG30	 SDF25/20 SDF25/20

* Profile 00a replaced by profile 00c ** Profile 00aGA replaced by profile 00cGA Profile tube: H = Hardened, V = heat-treated


IDENTIFICATION GUIDE FOR DRIVE SHAFTS



Size	Cross and bearing kit	Yoke	Replaced by size	Profile pairing	*Guard tubes	*guard cones
IDENTIFICATION GUIDE FOR TYPES PHASED OUT (Individual components only conditional available)						
WI			W 2300			
WII			W 2400			
W 220			W 2400			
WWE/MWZ 2270			WWE/MWZ 2280			
WWE/MWZ 2370			WWE/MWZ 2380			
WWE/MWZ 220			WWE/MWZ 2480			

*SC 04/14/24/34 interchangeable with SC/SD 05/15/25/35 ** Profile 00aGA replaced by profile 00CGA

CONNECTING PROFILES



DIMENSIONS FOR GUARD TYPE

	SC SD		SC/SD05 D = 47	SC/SD15 D = 58	SC/SD25 D = 70	SC/SD35 D = 90
	PG				PG25 D = 70	
	PG		PG20 D = 85		PG30 D = 104	

**FOR ALL REPAIRS USE ONLY ORIGINAL
WALTERSCHEID SPARES.**